

# Adeprimaire

Water-based pasty  
elastomeric bitumen coating



- ▶ Safe for use in internal and confined areas, no dangerous vapours (no hydrocarbon solvent)
- ▶ High elongation and recovery
- ▶ High crack bridging
- ▶ Very good adhesion to concrete and PVC pipes
- ▶ Pasty compound for rough and porous surfaces
- ▶ No flowing when used vertically (thixotropic)
- ▶ Ready for use

## Packaging

- 25l can
- 2.5l can

## Main uses

- Waterproofing coating in confined areas: bathrooms, kitchens and wet areas.
- Façade damp proofing behind cladding and curtain walls.
- Bitumen primer for any Siplast membranes; advised for cold-applied self-adhesive systems in internal areas.

## Description

- Polymeric bitumen pasty emulsion, additives, water.
- Sensitive to frost.
- Colour: black when dry.
- Solvent-free (non flammable product).

## Complementary information

Product technical information.

## Customs nomenclature

2713 20 00 00 00 T

## Application

- During storage and application, temperature (product, support and air) must be  $> 5^{\circ}\text{C}$ .
- Liquefy the gel by mixing with a spatula.
- Simple application using roller, brush, squeegee, trowel, spatula, brush or roller.
- Application must be done on clean and dry support.
- The coating thickness can be lightly different according to the used application equipment.

Consumption varies according to the substrate roughness and type of application:

- foundations and facades;
- wet internal areas: bathrooms, kitchens ( $< 25\text{m}^2$ );
- as primer, to be diluted in water;
- Drying time (at  $23^{\circ}\text{C}$ ): approx. 24h.

In all cases, this product must be used in accordance with the relevant technical specifications.

## Safety

**Adeprimaire** is not rated as dangerous (for the applications described in this document).

This document is only a guide. Siplast-Icopal reserves the right to change the composition and fixing recommendations of products as a result of evolution of knowledge and technology.



12, rue de la Renaissance  
F-92184 Antony Cedex  
Tél. +33 (0)1 40 96 35 00  
Fax. +33 (0)1 46 66 24 85  
www.siplast-international.com

ISO 9001

BUREAU VERITAS  
Certification

L'ensemble des sites de la Société

