

Product Technical Information

ITA/ATEXP/539

REV 01 – 24/06/10

1/1

ASSOUR CHAPE +

DEFINITION

Thin sound-deadening underlay for floating screeds with incorporated adhesive selvedge.

Main uses :

Underlay for floating screeds or slabs for sound-proofing flooring against impact noise and making it possible to attain the various required performance levels.

COMPOSITION

Glass fibre matt surfaced with a bituminous compound and a plastic film. Incorporated selvedge consisting of a translucent and adhesive strip.

- Weight/m² : approximatly 750 g
- Surface : plastic film with self adhesive selvedge
- Sous-face : glass fiber matt



PRESENTATION

- Thickness : 3,2 mm ± 0,5 mm
- Thickness dB : 2,5 mm (NF EN 12431) – report CSTB HO 06-034
- Length : 20 m ± 0,2m
- Width : 1 m ± 0,01m (without selvedge)
- Weight of a roll : approximatly 15 kg
- Rolls per pallet : 16

APPLICATION

The application of ASSOUR CHAPE + has to be in accordance with DTU 26.2, 52.1 and NF P 61-203.

This product is classified **SC1 b2 A** (certificat **CSTBat n°02a-02**)

SECURITY

It is not classified as dangerous according to the international regulation.

ISO 9001 CERTIFICATION

Our company has ISO 9001 certification for all our plants in France.

