

Product Technical Information

ITA/ATEXP/411

REV 0 – 18/02/10

1/1

ASSOUR PARQUET

DEFINITION

Thin sound-deadening underlay for floating wood parquet or floating laminated flooring.

Main uses :

- Intended for laying under floating full-surface bonded parquets or under laminated flooring for private premises.
- On new substrates : concrete slab, dry screed, wood panels, plywood, particle board, OSB boards, ...
- On old hard flooring : stones, marble, tiling, ...



COMPOSITION

Glass fiber matt surfaced with a bituminous compound and a plastic film. Incorporated selvedge consisting of a translucent and adhesive strip.

- Weight/m² : approximatly 750 g
- Surface : plastic film
- Underface : Glass fiber matt (300 g/m²)

PRESENTATION

- Thickness : 3,5 mm ± 0,5 mm
- Length : 10 m ± 0,1 m
- Width : 1 m ± 0,01 m
- Weight of a roll : approximatly 7,8kg
- Rolls per pallet : 28

APPLICATION

Thin sound-deadening under layer to be applied below laminated floor covering, parquets, ...
The application of ASSOUR PARQUET has to be in accordance with NF P 63-204 (DTU 51.11).
La pose de l'ASSOUR PARQUET suit les préconisations du DTU 51.11 (NF P 63-204).

SECURITY

It is not classified as dangerous according to the international regulation.