

Dalle Parcours®

Walkways tiles for inaccessible flat roofs



- ▶ High mechanical resistance
- ▶ Protects the waterproofing
- ▶ Protects the insulation due to its ability to spread the stresses due to foot traffic
- ▶ Repaired by simple replacement of a new tile
- ▶ Economical: only the areas subject to maintenance traffic need to be protected
- ▶ Easily fixed by cold or hot bonding, easily cut with a sharp knife
- ▶ Walkways can be differentiated by using an alternative colour

Packaging

- 0.50m x 0.50m tiles (2.5kg each)
 - Wrapped in packs of 12 tiles (3m² – 32kg)
 - Pallet of 36 packs: 108m² – 1,200kg
- Colours:** see data sheet "Colours on your roofs".

Main uses

- Walkways and other areas of maintenance foot traffic on flat roof waterproofing, bonded directly onto self-finished roof waterproofing.

Description

- Semi-rigid tile: 0.50m x 0.50m
- Thickness: 6mm
- Bitumen with limestone filler: 9.0kg/m²
- Double glass mat reinforcement: 50g/m² x 2
- Surfaced with ceramic granules or slate flakes
- Underside: polyester film 15g/m²

Performances

- Resistant to detachment from a vehicle of 180kg rolling at 30km/h
- Fire classification: T 30/1 (CSTB N° 82 18331)

Application

- Cold bonding, see photo 1
- Hot bonding, see photo 2

Complementary information

- Avis Techniques des revêtements d'étanchéité autoprotégés associés, de type Adepar, Paradiene, Paradiene S, Paracier FM, Paracier soudable, Parafor Solo, Parafor Solo FM, SCR Alliance Réfection, Vermetal.

Customs nomenclature

- 68.07.10.19.0.00.0.P

Safety

Dalle Parcours is not rated as dangerous (for the applications described in this document).

This document is only a guide. Siplast-Icopal reserves the right to change the composition and fixing recommendations of products as a result of evolution of knowledge and technology.

