

# Galba by Icopal

## Technical Product Data



### Pitch

Minimal pitch	12°
Maximal pitch	90°

### Dimensions

Size of tile - overall (w x h)	1324mm x 410mm
Size of tile - cover (w x h)	1260mm x 369mm (6 module tile/each module 210mm wide)
Coverage	0,465 m <sup>2</sup> per element (2,15 elements per m <sup>2</sup> )
Thickness steel	0,43mm
Type of steel + composition	Aluzink 150 g/m <sup>2</sup>

### Weight

Weight per element	3,1 kg
Weight per m <sup>2</sup>	6,7 kg

### Fixings

Decra® fixings	Decra® fixing recommended
Fixings per element	4 pieces (10 per m <sup>2</sup> )

### Battens

Batten distance	369mm
Center distance battens (max.)	Minimal batten thickness (recommended)
600mm	38mm x 30mm (h x w)
900mm	50mm x 30mm (h x w)
1200mm	50mm x 50mm (h x w)

### Usage

See installation guide	
------------------------	--

### Weather resistance


Snow load	Until 1400 kg/m <sup>2</sup>
UV-resistant	Colourfast
Waterproof at:	A pitch of 12° rain intensity 2 L/m <sup>2</sup> at a wind speed of 14 m/sec
Noise (directly under the roof during heavy rain)	Li = 65 dB




### Package

Elements per pallet	0,43mm steel 320 elements
---------------------	------------------------------

## Composition

### Galba by Icopal



-  Natural stone granulate
-  Coloured acrylic resin
-  Aluzink 150 g/m<sup>2</sup> steel

## Colours



Teak (03)



Shiny Black (17)



Red Mediterranean (24)